

### DESCRIPTION

FSP2000-A0AGPBI is an industrial level of switching power supply. The power supply comes to offer the total power capacity up to 2000 Watts, and uses unique active PFC (Power Factor Correction) circuit design with its high-load electrical components, makes it to be perfectly used in an industrial, especially high wattages environment. In addition, with its full range of input and output electrical features, the power supply is ideally the best choice for server, workstation, communication or any other automation applications to use. The product also complies with the latest safety and EMC standards, which is perfectly to meet various regulations worldwide.



### APPLICATION

For standard, advanced workstation, server and industrial power system.

### FEATURES

- 80 PLUS Platinum
- Low Ripple & Noise
- Output over voltage protection
- Short circuit protection on all outputs
- Resettable power shut down
- 16 x PCI-E 6+2 PIN
- INTERNAL 12 cm fan 100% burn-in under high ambient temperature(50°C)
- Vacuum-impregnated transformer
- MTBF:100K hours at 25°C
- 100% Hi-pot tested Line input fuse protection

### WATTAGE

**Wattage:** 2000W

### DIMENSION

**Dimension:** 200mm(L) x 150mm(W) x 86mm(H)

### PRODUCT HIGHLIGHT

**Efficiency Level:** 80 Plus Platinum  
**Altitude:** 5000M

### INPUT SPECIFICATION

**Input Range:** 90-264 Vac  
**Input Frequency:** 47-63 Hz  
**Input Current:** 115V@ 15.0 Amps-rms maximum  
 230V@ 12.0 Amps-rms maximum

### GENERAL SPECIFICATION

**Efficiency:** 92% @ 115V / 93% @ 230V  
**Voltage** +3.3V, +12V, +5V, +5SB: ±5%  
**Regulation:** -12V: ±10%

### \*Output Voltage and Current Rating

	+3.3V	+5V	+12V1	+12V2	+12V3	+12V4	+12V5	+12V6	-12V	+5Vsb
<b>Ripple-Noise(R-P) mV</b>	50mV	50mV	120mV	50mV						
<b>Regulation Load %</b>	±5%	±5%	±5%	±5%	±5%	±5%	±5%	±5%	±10%	±5%
<b>Output Max.(A)</b>	25A	25A	30A	30A	30A	30A	30A	30A	0.5A	4A
<b>Output Min.(A)</b>	0A	0.1A	0.2A	0.2A	0.2A	0.2A	0.2A	0.2A	0A	0A

### NOTES

- Maximum continuous total DC output power should not exceed 2000W.
- Maximum continuous combined load on +3.3DC and +5VDC outputs shall not exceed 150W.
- Ripple and noise measurements shall be made under all specified load conditions through a single pole low pass filter with 20MHz cutoff frequency. Outputs shall bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

This content is subject to change, please refer to specification for more detail.  
 FSP reserve the right to change the content without prior notice

### SAFETY STANDARD APPROVAL



### OUTPUT SPECIFICATION

**Hold up Time:** 115V/60Hz 17mSec.  
 Minimum@100% Load,  
 230V/50Hz 17mSec.

**Output Voltage Regulation:** Minimum,@100% Load  
 +3.3Vdc output : +3.76 Vdc minimum, + 4.8Vdc maximum  
 +5Vdc output : +5.75 Vdc minimum, + 7.0Vdc maximum  
 +12Vdc output : +13.5 Vdc minimum, + 15.5Vdc maximum

**Output Rise Time:** 115V-rms/230V-rms 5V  
 20ms Maximum  
 115V-rms/230V-rms 12V  
 20ms Maximum

**Ripple & Noise:** 3.3V:50mV p-p  
 5V:50mV p-p  
 12V1:120mV p-p  
 -12V:120mV p-p  
 5Vsb:50mV p-p

### ENVIRONMENTAL SPECIFICATION

**TEMP.Range:** Storage Temperature: - 20°C to + 80°C

**MTBF:** The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, maximum-output load, and nominal AC inout voltage